What belongs in a lone worker safety system?

Building a safety net that works for one person on site

When someone works alone, even a minor incident can become a serious emergency. A lone worker safety system is not a single device or an app; it is a planned set of measures that help protect that person from the moment a problem starts until help arrives. The right system depends on the work environment, the risks involved, and how quickly a worker can get assistance. But certain elements are essential in almost any situation.

The core of any system: a reliable alarm device

The most visible part of a lone worker safety system is the device the worker carries or wears. This needs to do more than just call for help. It should let the worker signal an emergency with a simple action, such as pressing a button, and it should also detect when something has gone wrong without the worker being able to press anything. A fall, a sudden period of no movement, or a man-down event are common scenarios where automatic alerting makes the difference between a quick response and a long delay.

The device must work wherever the worker goes. That means it needs a cellular connection that reaches into the areas where the person actually works, not just where the office has good signal. Battery life matters too: a device that needs charging every few hours is a liability. Look for a unit that can last through a full shift, and preferably longer, so the worker does not have to think about power during the day.

GPS location and mapping that actually helps

Knowing that someone needs help is only half the problem. The responder also needs to know where that person is. A good lone worker safety system includes GPS tracking that updates the worker’s location regularly, not just when an alarm is triggered. Some systems send a single location fix at the start of an alert, which can be misleading if the worker has moved since then or if the GPS signal was weak at that moment. Continuous or near-continuous tracking gives a much clearer picture.

Indoor work adds another layer of difficulty. GPS signals do not penetrate buildings well, so a system that relies only on satellite positioning may lose accuracy once the worker goes inside. Some devices supplement GPS with Wi-Fi positioning or cellular tower triangulation to maintain a reasonable location estimate indoors. For anyone who works in warehouses, factories, or multi-storey buildings, this is a detail worth checking.



MERCARI

Two-way voice communication for real-time assessment

An alarm tells the responder that something is wrong, but it does not say what. Two-way voice lets the responder talk to the worker directly, assess the situation, and decide on the right response. It also gives the worker a chance to explain what happened, which can reduce the need for a full emergency dispatch if the issue is minor. For the worker, hearing a human voice can be reassuring in a stressful moment.

Voice communication requires a clear audio path, which depends on the device's speaker and microphone quality and on the cellular network coverage at the worker's location. Testing the audio in the actual work environment is a good idea before relying on it. Background noise from machinery, wind, or traffic can make it hard for the responder to hear, and some devices handle that better than others.

Alert contacts and escalation paths

An alert that goes nowhere is useless. Every lone worker safety system needs a defined list of people who will be notified when an alarm is raised. This list should include more than one person, because the first contact might not be available. The system should try each contact in a set order, and if no one responds within a certain time, it should escalate to a backup or to a monitoring service.

Deciding who those contacts are is part of the safety policy for the business. They need to be people who can actually take action: someone who can call emergency services, someone who knows the work site, someone who can reach the worker if they are nearby. The system should let the business update these contacts easily, because people change roles and leave companies.

Monitoring options: in-house or outsourced

Someone has to watch for incoming alerts and respond to them. The business can handle this internally, with a designated person or team monitoring the system during work hours, or it can use an external monitoring service that operates around the clock. Each approach has trade-offs.

In-house monitoring gives the business direct control over the response. The person monitoring knows the workers, the site, and the procedures. But it also requires someone to be available and attentive at all times, which can be difficult for small teams or for shifts that run outside normal office hours. Outsourced monitoring provides consistent coverage without the staffing burden, but the business must ensure the monitoring centre has the information it needs to respond appropriately, such as site access details and emergency contact numbers.

Some systems offer a hybrid model where the business handles initial response during regular hours and a monitoring service takes over overnight or on weekends. This can be a practical middle ground for many small businesses.

Device setup and configuration that fits the job

A lone worker safety system is only effective if it is set up correctly for the specific work situation. That means configuring the device’s sensitivity for fall detection and man-down alerts, setting the check-in intervals if the system uses periodic check-ins, and making sure the device’s buttons and functions match what the worker can realistically use while wearing gloves or working in a confined space.



Some devices allow the business to adjust these settings through a web portal or an app, which is useful for fine-tuning the system without having to reprogram each unit individually. Others require manual configuration on the device itself, which can be time-consuming if there are multiple workers. The setup process should be documented clearly so that new workers or temporary staff can be added without confusion.

One resource that covers many of these considerations in a practical way is loneworkeralarms.co.nz, which focuses on wearable alarms designed for New Zealand conditions and provides details on device features and configuration options.

Testing and maintenance routines

A system that has never been tested is a system that might not work when it is needed. Regular testing should include checking that the device can connect to the cellular network, that the GPS location is reported correctly, that the alarm reaches the designated contacts, and that two-way voice is clear. Testing should happen on a schedule, and the results should be recorded so that any recurring issues can be spotted.

Batteries degrade over time, and firmware updates can change how a device behaves. Keeping the devices updated and replacing batteries before they fail is part of the ongoing maintenance. The business should assign someone to own this responsibility, because it is easy to overlook when no incidents have occurred.

Risk assessment as the foundation

Before buying any equipment, the business should conduct a risk assessment of the lone worker's tasks and environment. This assessment identifies the specific hazards the worker faces, the likelihood of each hazard leading to an incident, and the consequences if it does. The results of the assessment guide every decision about the safety system: what type of alarm device to use, what detection features are necessary, what communication methods are available, and what response procedures make sense.

A risk assessment also helps the business avoid over-investing in features that are not needed or under-investing in areas that pose the greatest risk. For example, a worker who spends most of their time in a vehicle may need a different setup than a worker who climbs ladders or works in a remote forest. The assessment should be reviewed regularly, because work conditions change, and new risks can appear.

Putting it all together into a safety policy

The lone worker safety system is not complete until it is written into a policy that everyone understands. The policy should state when the system must be used, how the worker activates it, what happens during an alarm, who is responsible for responding, and what the worker should do if the device malfunctions. It should also cover training: every worker needs to know how to use the device, how to test it, and what to expect when they raise an alarm.

The policy should be a living document, updated as the business grows, as new workers join, and as the work environment changes. A policy that sits in a drawer and is never looked at again is not much better than no policy at all.



For businesses looking for a practical starting point, loneworkeralarms.co.nz offers information on wearable alarms that include SOS, GPS, fall detection, man-down alerts, and two-way voice, with no mandatory monitoring fees, which can simplify the decision-making process for a small business that wants a straightforward system.

Procurement decisions that affect safety

Buying a lone worker safety system is not like buying office supplies. The decision affects how quickly a worker gets help in an emergency. It is worth taking the time to compare devices,

read the fine print on monitoring contracts, and ask about network coverage in the specific areas where the worker will be. Some systems lock the business into a long-term monitoring contract, while others let the business choose how and when to monitor. Understanding these trade-offs before purchasing prevents surprises later.

A small business does not need a complex enterprise system, but it does need a system that is reliable, easy to use, and properly matched to the risks its workers face. Getting those basics right makes the difference between a system that sits in a drawer and a system that saves time, money, and potentially a life.